### **Product Data Sheet**

# Earthborn Casein Filler



#### 1. Use

**Earthborn Casein Filler** is suitable for sound, absorbent surfaces to level unevenness and to fill holes, cracks and gaps. It is used prior to painting with **Earthborn** Wall & Ceiling Paints.

#### 2. Product Codes

500g 1.1811 2kg 1.1812

# 3. Coverage

1.5 kg per m<sup>2</sup> per mm of thickness of coating

#### 4. Colour

White

## 5. Drying Time

Approx. 4 hours, ready for sanding down after 8-12 hours.

### 6. Instructions for Use

The surfaces should be clean and grease-free. Water-soluble old coats of distempers or lime-paints must be removed. Any loose material should be brushed off. 1 kg of Filler should be mixed with 150 ml water until a lump-free paste is obtained. If necessary add some water during application.

If colouring the filler with Earthborn pigments, the dry powder must be carefully mixed with the pigment first then the required water added. Apply the ready-mixed filler to create an even surface. If necessary level-out deep holes and cracks a second time.

**Note:** The whitening and covering power will only be visible when the product is fully dry.

## 7. Tools

Spatula or knife

## 8. Storage

Cool, dry, frost-free

## 9. Ingredients

Powdered marble, lime hydrate, white cement, cellulose, clay, casein

## 10. Safety

Alkaline. Irritating to eyes and skin. Keep out of the reach of children.

### 11. Disposal

Allow unused paint to dry and dispose of safely according to local authority disposal guidelines.

The user is recommended to test the product on the intended surface to ensure its suitability

Earthborn Paints Frodsham Business Centre Bridge Lane Frodsham Cheshire WA6 7FZ

Tel: 01928 734171 www.earthbornpaints.co.uk