

1. Use

Earthborn Wall Glaze is a water-based, transparent glaze for interior use. It provides a washable, protective glaze for walls painted with Earthborn Claypaint and Earthborn Ecopro Emulsion. Mixed with Earthborn Pigment it is suitable for all broken work (e.g. sponging, marbling, wood-graining) or as a colour wash.

2. Colours and Product Codes

750ml & 2.5L Clear

3. Coverage

When diluted and used as a glaze: 50 square metres per litre.

4. Preparation

The surface should be smooth, clean, dust/grease free, absorbent and dry. Previously glossed or varnished surfaces must be thoroughly sanded prior to application.

5. Drying Time

Dependent on internal temperature, humidity and the amount of water added to the Wall Glaze

6. Properties

Earthborn Wall Glaze is a water-based, transparent glaze. It protects surfaces from dust and provides a durable, washable surface.

7. Application

Stir thoroughly before use.

Glaze: Seal and protect painted surfaces with a mix of water and Earthborn Wall Glaze (recommended ratio 1 part Wall Glaze to 3 parts water).

Broken colour work: Make a solution of Earthborn Pigment by adding approximately 100ml of water to the desired quantity of Pigment and leave to soak for up to 30 minutes. Mix the resultant solution with more water if necessary and then add Earthborn Wall Glaze (recommended ratio 1 part Wall Glaze to 4 parts solution). Apply to surface using sponge, brush or other desired technique.

Colour wash: Mix Earthborn Wall Glaze and Pigment using the proportions and method described for Broken Colour Work. Spread the resultant colour wash onto a dry base coat of emulsion with a brush or a natural sponge and blend, if desired, using a dry paintbrush. Work diagonally starting in a top corner. For best results apply more than one colour wash, varying the colour as desired.

8. Cleaning

Wash tools with warm water.

9. Storage

Keep containers tightly sealed and store in a cool, dry and frost-free place.

Shelf life is 6 months for unopened containers.

10. Safety

Please see Material Safety Data Sheet

11. Ingredients

Water, cellulose, clays, vinegar ester, 0.1% preservative.

The user is recommended to test the product on the intended surface to ensure its suitability.