

# Ecopro Eggshell

## 1. What is Earthborn Ecopro Eggshell?

Earthborn Ecopro Eggshell is a durable, washable, scuff resistant environmentally friendly paint. The unique formulation is totally oil and acrylic free and contains minimal VOCs. Suitable for use on interior walls, ceilings and woodwork.

## 2. Coverage

Approximately 14M<sup>2</sup>

## 3. Properties

Earthborn Ecopro Eggshell is totally free from oils, acrylics and is virtually VOC free. It has a high solids content which gives it excellent covering properties and makes it easy to apply. Suitable for use on internal walls, ceilings and wood work.

## 4. Preparation

Surfaces must be dry, clean and free of dust and grease. All unstable surfaces, including water-soluble distempers, should be removed or washed off. Stains that migrate through the paint and areas of acrylic or silicone filler should first be treated with Earthborn Isolating Primer. Timber surfaces should be prepared with Earthborn Multi Purpose Primer and lightly sanded prior to application. Previously painted surfaces should be sanded to provide a key, then primed with Earthborn Multi Purpose primer. Avoid the inhalation of dust. Wear a suitable face mask / protective equipment if dry sanding or using spray equipment.

## 5. Application

Do not apply in temperatures below 8°C. Always stir before use. On prepared timber, apply liberally and evenly with a brush or roller, finishing in the direction of the wood grain. On walls and ceilings, apply in the usual manner with a brush or roller. For highly absorbent surfaces such as new plaster, apply an initial mist coat of Earthborn Ecopro Matt Emulsion (4 parts paint to 1 part water). Two coats are normally required.

## 6. Colour

Available in the full BS4800 colours plus black and white.

## 7. Drying Time

In normal temperatures and humidity, allow 6 - 12 hours drying time between coats. The eggshell is touch-dry after 1-2 hours. Maximum durability is achieved after 10 days.

## 8. Cleaning

Remove as much product as possible from brushes or roller, before cleaning. Clean tools in water. To minimise water usage please avoid cleaning under running water.

## 9. Storage

Keep containers tightly sealed and store in a cool, dry and frost-free place. Unopened containers have a shelf-life in excess of 6 months.

## 10. Safety

Please refer to the Material Safety Data Sheet

## 11. Ingredients

Water, Chalk, Talcum, Binder, Titanium Dioxide, Phosphate, Sodium Hydroxide, 0.1% synthetic preservative (Methylcellulose)

## 12. Disposal

Although Earthborn Ecopro Emulsion is biodegradable, do not empty into watercourses or drains, or into a waste bin. Minimise paint wastage by estimating how much paint you will need. Recover unused paint for re-use. Reuse of paint can effectively minimise the products' life cycle environmental impact.

## 13. VOC content

This products has a VOC content of less than 0.5g/L

### Note:

*Our colours are made using a traditional batch process so there may be slight colour variations between batches and the colour chart. Whilst every precaution is taken to ensure colour continuity, please make sure you have sufficient paint from the same batch to complete your work.*

*The user is recommended to test the product on the intended surface to ensure its suitability*