

Earthborn Eco Chic is Claypaint for painting furniture. It is virtually VOC free and has no unpleasant odours or emissions.

Licensed to carry the EU Ecolabel (Licence No DE/044/054)

1. Coverage

Approximately 10m² per litre.

However, coverage is dependent on absorbency of substrate and application technique.

2. Colours

Earthborn Claypaint is available in 72 standard colours.

3. Pack Size

750ml.

4. Thinner (Depends on product if needed)

Water.

5. Uses

Earthborn Claypaint is ideal for painting wooden furniture.

6. Ingredients

Water, Filler (Various Clays, Chalk, Kaolin), vinegar ester, Thickener (Methylcellulose), various pigments, 0.1% synthetic preservative* (Isothiazolinone Mixture). Some colours contain Titanium Dioxide and various pigments.

TiO₂ and Colourant Free colours: Marbles, Humpty Dumpty, Freckle & Flower Pot

TiO₂ Free colours: Trilby, Hidey-Hole, Muddy Boots, Rocky Horse, Can-Can, Lady Bug, Trumpet, Toy Soldier, Bobble Hat, Cricket, Hobby Wood, Hobgoblin, Grassy.

7. Properties

Earthborn Claypaint has exceptional opacity and dries to a luxurious matt finish.

8. Preparation

Previously painted furniture should be given a light sanding to provide a key. No need for a primer.

If painting directly onto untreated wood, prime with Earthborn Claypaint, thinned with 20% water.

Finish with a protective coating of Earthborn Furniture Wax or Furniture Glaze

9. Instructions for Use

Stir before use. Do not apply in temperatures below 8°C. For best results use and synthetic bristle brush.

10. Application

Try applying a contrasting base coat followed by your chosen topcoat colour, then sand back areas to reveal the colour beneath. For more ideas visit www.earthbornpaints.co.uk

11. Colouring

N/A

12. Drying Time

Allow 6-12 hours between coats, depending on room temperature and relative humidity. Fully cured after about 10 days.

13. Tools

Brush, roller or spray.

14. Cleaning

Clean rollers, brushes and tools using warm soapy water immediately after use.

15. Maintenance

The term washable (DIN53778) refers to the durability of the paint and its resistance to abrasion. It is often possible to remove surface marks using a pencil eraser or very fine emery paper (test on a small area first).

16. Storage & Disposal

Keep containers sealed and store in a cool frost-free place.

Dispose of contents / container in accordance with local / national regulations.

17. Safety

No hazard or risk groups. Please refer to Material Safety Data Sheet

18. Water Vapour Permeability

Sd value = 0.02m

19. Moisture Vapour Transmission

MVT value = 1115g/m² per 24hours

20. VOC Content

This product has a VOC content of less than 0.5g/l

21. Safety of Toy Standards (EN71-3:2019)

NB: The user is recommended to test the product on the intended surface to ensure its suitability.

**Synthetic preservative Contains*

Contains 1,2-benzisothiazol-3(2H)-one, Reaction mass of 5-chloro-2-methyl-1,2-thiazol-3(2H)-one and 2-methyl-1,2-thiazol-3(2H)-one(3:1). May produce an allergic reaction.

Please see MSDS for more details



Updated on 28/06/2022