

**Earthborn Eco Chic** is Claypaint for painting furniture. It is virtually VOC free, and has no unpleasant odours or emissions. Licensed to carry the EU Ecolabel (Licence No UK/044/001)

## 1. Coverage

Approximately 10m<sup>2</sup> per litre.

However, coverage is dependent on absorbency of substrate and application technique.

## 2. Colours

Earthborn Eco Chic is available in 72 standard colours.

## 3. Pack Size

750ml

## 4. Thinner (Depends on product if needed)

Water

## 5. Uses

Earthborn Eco Chic is ideal for painting wooden furniture.

## 6. Ingredients

Marbles, Humpty Dumpty, Freckle & Flower Pot: Water, various clays, chalk, kaolin, vinegar ester, methylcellulose, various pigments, 0.1% synthetic preservatives.

Other colours: Titanium Dioxide and various pigments.

## 7. Properties

Earthborn Claypaint has exceptional opacity and dries to a luxurious matt finish.

## 8. Preparation

Previously painted furniture should be given a light sanding to provide a key. No need for a primer.

If painting directly onto untreated wood, prime with Eco Chic Claypaint, thinned with 20% water.

Finish with a protective coating of Earthborn Furniture Wax or Furniture Glaze

## 9. Instructions for Use

Stir before use. Do not apply in temperatures below 8°C. For best results use and synthetic bristle brush.

## 10. Application

Try applying a contrasting base coat followed by your chosen top coat colour, then sand back areas to reveal the colour beneath. For more ideas visit [www.earthbornpaints.co.uk](http://www.earthbornpaints.co.uk)

## 11. Colouring

N/A

## 12. Drying Time

Allow 6-12 hours between coats, depending on room temperature and relative humidity. Fully cured after about 10 days.

## 13. Tools

Brush, roller or spray.

## 14. Cleaning

Clean rollers, brushes and tools using warm soapy water immediately after use.

## 15. Maintenance

The term washable (DIN53778) refers to the durability of the paint and its resistance to abrasion. It is often possible to remove surface marks using a pencil eraser or very fine emery paper (test on a small area first).

## 16. Storage & Disposal

Keep containers sealed and store in a cool frost-free place.

Dispose of contents / container in accordance with local / national regulations.

## 17. Safety

No hazard or risk groups. Please refer to Material Safety Data Sheet

## 18. Water Vapour Permeability

Sd value = 0.02m

## 19. Moisture Vapour Transmission

MVT value = 1115g/m<sup>2</sup> per 24hours

## 20. VOC Content

This product has a VOC content of less than 0.5g/L

## 21. Safety of Toy Standards (EN71-3:2019)

*NB: The user is recommended to test the product on the intended surface to ensure its suitability.*

*\*Synthetic preservative Contains*

Contains 1,2-benzisothiazol-3(2H)-one, Reaction mass of 5-chloro-2-methyl-1,2-thiazol-3(2H)-one and 2-methyl-1,2-thiazol-3(2H)-one(3:1). May produce an allergic reaction.

*Please see MSDS for more details*

